

Attach the tip of lenses and use for adjustment of a peak transmittance, prevention from reflection, and reduction of the brightness without changing wavelength.



■UV cut filter (Protection cover filter)		
Model	Filter	Screw size
UV225	UV-CUT	22.5
UV255	UV-CUT	25.5
UV270	UV-CUT	27.0
UV305	UV-CUT	30.5
UV225M	UV-CUT(Multi cour)	22.5
UV255M	UV-CUT(Multi cour)	25.5
UV270M	UV-CUT(Multi cour)	27.0
UV305M	UV-CUT(Multi cour)	30.5



■IR cut filter		
Model	Filter	Screw size
IR225	IR-CUT(C500S)	22.5
IR255	IR-CUT(C500S)	25.5
IR270	IR-CUT(C500S)	27.0
IR305	IR-CUT(C500S)	30.5



■Polarized filter		
Model	Filter	Screw size
PL225	PL225	22.5
PL225R	PL255 Rotation type	25.5
PL270R	P270 Rotation type	27.0
PL305R	PL305 Rotation type	30.5



■Quarter wave plate		
Model	Filter	Screw size
QWT340R	1/4P 305 Rotation type	34



■Color filter		
Model	Filter	Screw size
B225	Blue(B390)	22.5
B255	Blue(B390)	25.5
B270	Blue(B390)	27.0
B305	Blue(B390)	30.5
G225	Green(G583)	22.5
G255	Green(G583)	25.5
G270	Green(G583)	27.0
G305	Green (G583)	30.5
Y225	Yellow(Y480)	22.5
Y255	Yellow(Y480)	25.5
Y270	Yellow(Y480)	27.0
Y305	Yellow(Y480)	30.5
YA405	Orange(YA3)with MC	40.5
R225	Red(R62) (R60)	22.5
R255	Red(R62) (R60)	25.5
R270	Red(R62) (R60)	27.0
R305	Red(R62) (R60)	30.5
R405	Red(R62) (R60)	40.5



■ND filter		
Model	Filter	Screw size
ND2225	ND2(50%)	22.5
ND2255	ND2(50%)	25.5
ND2270	ND2(50%)	27.0
ND2305	ND2(50%)	30.5
ND2405	ND2(50%)	40.5
ND4225	ND4(25%)	22.5
ND4255	ND4(25%)	25.5
ND4270	ND4(25%)	27.0
ND4305	ND4(25%)	30.5
ND4405	ND4(25%)	40.5
ND8270	ND8(12.5%)	27.0
ND8305	ND8(12.5%)	30.5

*Filters not listed in the catalogue are available as custom order.